



RockerBT V2

Bluetooth Controller Rocker Switch

OWNER'S MANUAL


ATTENTION:
WATCH THIS VIDEO BEFORE FIRST USE!

Who reads manuals?

Scan the **QR code** or go to **rockvillesupport.com/rockerbt-v2** to access how-to video(s), the owner's manual, and other important information you may need to get the most out of your item.

If you prefer written instructions, please read ahead!

With Rockville you get many options.




RockvilleAudio.com

© 2022 ROCKVILLE // Features and specifications are subject to change and or improvement without notice

Missing items? If you ordered a bundle that includes more than one product and you are missing part of your bundle, then it just means your order shipped from two different warehouses. You will receive the remaining items very soon. If you have any concerns or inquiries, feel free to call our customer support center at 1-646-758-0144, 24 hours a day/7 days a week.

Thank you for purchasing this Rockville RockerBT V2 Bluetooth Controller Rocker Switch. Please read this owner's manual carefully for proper use of your Rockerbt V2. Should you need assistance, please call our technical help line at 1-646-758-0144, 24 hours a day/7 days a week.

Functions



1. Previous track
2. Next track
3. Power
4. Play/pause
5. Volume down
6. Volume up

Installation

The RockerBT V2 is designed to snap into a standard Carling style switch opening. These are commonly used in the dashboards of many automobiles and off-road vehicles.

Wiring

Ignition (+12V), Red Wire: Connect to the ignition or positive (red) post of the battery.

Ground (-), Black Wire: Connect to the any bare metal part of vehicle chassis or negative terminal of the battery.

Remote Out, Blue Wire: Connect to you amplifier's remote terminal. Now the amp will power on whenever the RockerBT V2 is powered on.

3.5mm Pre-Out, Black Cable: Connect to amplifier's input.

3.5mm Line In, Black Cable: Connect any device with a 3.5mm output.

Operation

Bluetooth

1. Press the power button. The unit features blue back lighting and it will flash red/blue alternately indicating the RockerBT V2 is in pairing mode and ready to use.
2. In your device's Bluetooth list of available devices search for and select RockerBT V2.
3. The RockerBT V2 is now paired to your device. Please note, the unit will remember and automaticlaly connect to the last paired device.

Auxilliary Input

Plugging a 3.5mm jack into the 3.5mm Line In port will put the unit in AUX mode. In this mode, the RockerBT V2 will only control volume. All other playback functions are done via the input source. Please note that plugging a jack into the 3.5mm input will automatically override Bluetooth mode. To return to Bluetooth mode, you must first unplug any input source connected to the 3.5mm input.

Features

- Remote output allows you to turn any amplifier on or off
- Simple 5-Button operation: Play/pause, previous/next track, volume up/down, and power on/off
- Mounts into a standard carling rocker switch opening
- 3.5mm Aux input
- 3.5mm Aux output
- Volume controls BT & AUX input
- Replaces head unit and works with any amplifier
- Perfect for Polaris/ATV/UTV/RZR/golf carts, boats, and more
- Marine Grade Protection: Meets or exceeds the American Boat and Yacht Council (ABYC) marine electronics standards and the American Society for Testing and Materials (ASTM)
- Bluetooth v4.0
- Hassle-free Bluetooth auto-pairing
- Power and ground connections
- Back-lit buttons for easy use day or night
- Dimensions (W x H x D): 1.04" x 2.02" x 2.64"